

Magnification of the macro extension tube

The shooting distance and shooting magnification change according to the position of the focus ring.

The following table shows reference values for when the focus ring is on the nearest side.

If the surroundings are blurred, please use the narrow aperture.

		Lens Only			MCEX-18G Mounted			MCEX-45G Mounted		
	Lens	Max.Magnification	Working distance(mm)	Shortest shooting distance(mm)	Max.Magnification	Working distance(mm)	Shortest shooting distance(mm)	Max.Magnification	Working distance(mm)	Shortest shooting distance(mm)
Prime	GF23mmF4 R LM WR	0.09	249	380	0.85	11	160			
	GF45mmF2.8 R WR	0.14	334	450	0.53	85	219	1.13	40	201
	GF63mmF2.8 R WR	0.17	401	500	0.46	172	288	0.88	105	249
	GF110mmF2 R LM WR	0.16	747	900	0.33	411	582	0.59	274	473
	GF120mmF4 R LM OIS WR Macro	0.50	273	454	0.71	223	422	1.04	187	412
	GF250mmF4 R LM OIS WR	0.22	1,169	1,400	0.31	897	1,147	0.44	697	973
Zoom	GF32-64mmF4 R LM WR	Wide	0.08	356	500	0.66	27	189	1.52	0
		Tele	0.12	427	600	0.44	90	281	0.91	22
										Shooting inability area

Working Distance: Distance from the top of the lens barrel to the subject

Shortest shooting distance: Distance from the image sensor to the subject